



Stavitelná vodící pouzdra s vložkou z tvrdokovu

Typ pouzdra	ø d [mm]	ø D [mm]	Závit G	Délka L [mm]	Úhel α	Rozsah upínacích pr m r do		D lení po
F 351	9	13	M 8 x 0,6	50	30	0,7	5,5	0,1
I 351	9	12,5	M 8 x 0,75	44	16	0,7	6,0	0,1
F 352	11	15	M 10 x 0,6	50	30	1,0	7,5	0,1
I 352	11	14,5	M 10 x 0,8	53	16	1,0	7,0	0,1
F 3001	11	14,5	M 10 x 0,75	53	16	1,0	7,0	0,1
F 103	12	16	M 12 x 1	50	30	1,0	7,5	0,1
T 340	13	16	M 12,5 x 0,75	41,5	15	1,0	8,0	0,5
T 330	14	18	M 13 x 0,75	63	16	1,0	9,0	0,5
I 353	16	19,5	M 14 x 1	59	16	1,0	10,0	0,1
F 850	16	20	M 16 x 1	52	30	1,0	12,0	0,1
F 853	18	22	M 16 x 1	61	30	1,0	13,0	0,1
F 104	20	24	M 20 x 1	55	30	2,0	13,0	0,1
T 221	21	24	M 18 x 1	57,5	12	3,0	15,0	0,5
I 354	22	29	M 19 x 1	68	16	2,0	16,0	0,5
F 391	22	29	M 22 x 1	68	16	3,0	18,0	0,5
F 605	24	29,5	M 24 x 1	61	30	2,0	17,0	0,5
T 223	28	34	M 25 x 1	82	16	3,0	21,0	0,5
I 357	28	38	M 25 x 1	81	30	3,0	21,0	0,5
F 355	32	39	M 32 x 1	71	30	3,0	22,0	0,5
T 227	34	41	M 34 x 1	87,5	10	3,0	25,0	0,5
F 854	40	48	M 36 x 1	71	30	3,0	26,0	1,0
F 105	40	48	M 40 x 1	71	30	3,0	26,0	1,0
T 229	42	49	M 40 x 1	82	16	3,0	32,0	1,0



Všechna pouzdra dodáváme i s upínacím otvorem pro 4-hran nebo 6-hran



Všechna vodící pouzdra dodáváme též s prodlouženou vložkou z tvrdokovu nebo v mezirozmích